



Artikel-Nr.	Rohrinnenweite DN		Rohr- nennweite DN	Metallbalg Werkstoff: 1.4541		Werkstoff Nahtloses Rohr nach DIN 17456 / 17458			Baulänge ± 3-5% [mm]		
	[mm]	S* [mm]		Innen- Ø [mm]	Außen- Ø [mm]	1.4301	1.4541	1.4571			
HTS-10-04-4-S	4,00	X1,00		6	10	X	X	X	> 10		
HTS-10-04-5-S	5,00	X1,00		6	10	X	X	X	> 10		
HTS-10-04-6-S	6,00	X0,50		10	15	X			> 10		
		X1,00				X	X	X			
		X1,50				X	X	X			
		X2,00				X	X	X			
HTS-10-04-7-S	7,00	X1,00		10	15	X		X	> 10		
HTS-10-04-8-S	8,00	X0,50		12	19	X			> 10		
		X1,00				X	X	X			
		X1,50				X	X	X			
		X2,00				X	X	X			
HTS-10-04-9-S	9,00	X1,00		12	19	X		X	> 10		
HTS-10-04-10-S	10,00	X1,00		16	22	X	X	X	> 10		
		X1,50				X	X	X			
		X2,00				X	X	X			
		X2,50				X		X			
	X3,00						X	X			
HTS-10-04-10,2-S	10,20	X1,60		16	22	X			> 10		
		X2,00				X	X	X			
HTS-10-04-11-S	11,00	X1,50		16	22		X		> 10		
HTS-10-04-12-S	12,00	X1,00		20	29	X	X	X	> 10		
		X1,50				X	X	X			
		X2,00				X	X	X			
		X2,50				X	X	X			
		X3,00				X	X	X			
	X4,00					X	X	X			
HTS-10-04-13-S	13,00	X1,00		20	29	X			> 10		
		X1,50				X					
		X2,50				X					
HTS-10-04-13,50-S	13,50	X1,60		20	29	X			> 10		
		X2,00				X					
		X2,30				X					
		X2,60						X		X	X
		X2,90						X		X	X

Artikel-Nr.	Rohr-nennweite DN		Rohr-nennweite DN [inch]	Metallbalg Werkstoff: 1.4541		Werkstoff Nahtloses Rohr nach DIN 17456 / 17458			Baulänge ± 3-5% [mm]
	[mm]	S* [mm]		Innen- Ø [mm]	Außen- Ø [mm]	1.4301	1.4541	1.4571	
HTS-10-04-13,72-S	13,72	X2,24 X3,02		20	29	X X			> 10
HTS-10-04-14-S	14,00	X1,00 X1,50 X2,00 X2,50 X3,00		20	29	X X X X X	X X X X X	X X X X X	> 10
HTS-10-04-15-S	15,00	X1,00 X1,50 X2,00 X2,50 X3,00 X4,00		25	36	X X X X X	X X X X X	X X X X X	> 10
HTS-10-04-16-S	16,00	X1,00 X1,50 X2,00 X2,50 X3,00 X3,50 X4,00 X5,00		25	36	X X X X X X X	X X X X X X X	X X X X X X X	> 10
HTS-10-04-17-S	17,00	X1,00 X1,50 X3,00		25	36	X X X	X X	X X X	> 10
HTS-10-04-17,14-S	17,14	X2,31 X3,20		25	36	X X			> 10
HTS-10-04-17,20-S	17,20	X1,60 X2,00 X2,30 X2,90 X3,20		25	36	X X X	X X X X X	X X X X X	> 10
HTS-10-04-18-S	18,00	X1,00 X1,50 X2,00 X2,50 X3,00 X3,50 X4,00		25	36	X X X X X X	X X X X X X	X X X X X X	> 10
HTS-10-04-20-S	20,00	X1,00 X1,50 X2,00 X2,50 X3,00 X3,50 X4,00 X5,00		32	44	X X X X X X X X	X X X X X X X X	X X X X X X X X	> 10
HTS-10-04-21-S	21,00	X3,00		32	44	X			> 10

Artikel-Nr.	Rohrinnenweite DN		Rohr- nennweite DN	Metallbalg Werkstoff: 1.4541		Werkstoff Nahtloses Rohr nach DIN 17456 / 17458			Baulänge ± 3-5% [mm]
	[mm]	S* [mm]		Innen- Ø [mm]	Außen- Ø [mm]	1.4301	1.4541	1.4571	
HTS-10-04-21,30-S	21,30	X1,60 X2,00 X2,60 X2,90 X3,20		32	44	X X X X X	X X X X X	X X X	> 10
HTS-10-04-21,34-S	21,34	X2,11 X2,77 X3,73 X4,75		32	44	X X X	X X X X	X X	> 10
HTS-10-04-22-S	22,00	X1,00 X1,50 X2,00 X2,50 X3,00 X4,00		32	44	X X X X X X	X X X X X X	X X X X X X	> 10
HTS-10-04-23-S	23,00	X1,50 X2,00 X4,00		32	44	X X	X	X X	> 10
HTS-10-04-24-S	24,00	X2,00 X3,50 X4,00		32	44	X X	X X	X X X	> 10
HTS-10-04-25-S	25,00	X1,00 X1,50 X2,00 X2,50 X3,00 X3,50 X4,00		40	53	X X X X X X	X X X X X X	X X X X X X	> 10
HTS-10-04-26,67-S	26,67	X2,11 X2,87 X3,91 X5,54		40	53	X X X	X X X X	X	> 10
HTS-10-04-26,90-S	26,90	X1,60 X2,00 X2,30 X2,60 X2,90 X3,20		40	53	X X X X	X X X X X	X X X X X	> 10
HTS-10-04-27-S	27,00	X3,00 X4,00		40	53	X X	X		> 10
HTS-10-04-28-S	28,00	X1,00 X1,50 X2,00 X2,50 X3,00 X3,50 X4,00 X5,00		40	53	X X X X X X X	X X X X X X X	X X X X X X X	> 10

Artikel-Nr.	Rohrinnenweite DN		Rohr- nennweite DN	Metallbalg Werkstoff: 1.4541		Werkstoff Nahtloses Rohr nach DIN 17456 / 17458			Baulänge ± 3-5% [mm]
	[mm]	S* [mm]		[inch]	Innen- Ø [mm]	Außen- Ø [mm]	1.4301	1.4541	
HTS-10-04-30-S	30,00	X1,00 X1,50 X2,00 X2,50 X2,60 X3,00 X3,50 X4,00 X5,00		40	53	X X X X X X X X X	X X X X X X X X X	X X X X X X X X X	> 10
HTS-10-04-32-S	32,00	X1,50 X2,00 X2,50 X3,00 X3,50 X4,00		40	53	X X X X X	X X X X	X X X X	> 10
HTS-10-04-33-S	33,00	X1,50 X4,00		40	53	X X	X	X	> 10
HTS-10-04-33,40-S	33,40	X2,77 X3,38 X4,55 X6,35		40	53	X X X X	X X X X	X	> 10
HTS-10-04-33,70-S	33,70	X1,60 X2,00 X2,60 X2,90 X3,20 X3,60 X4,05 X4,50		50	68	X X X X X X X	X X X X X X X	X X X X	> 10
HTS-10-04-34-S	34,00	X1,50 X2,00 X3,50 X4,00 X5,00 X5,50		50	68	X X X X X	X X X X	X X X X	> 10
HTS-10-04-35-S	35,00	X1,50 X2,00 X2,50 X3,00 X4,00 X5,00		50	68	X X X X X	X X X X	X X X X	> 10
HTS-10-04-36-S	36,00	X2,00		50	68	X		X	> 10

Artikel-Nr.	Rohr-nennweite DN		Rohr-nennweite DN	Metallbalg Werkstoff: 1.4541		Werkstoff Nahtloses Rohr nach DIN 17456 / 17458			Baulänge ± 3-5% [mm]
	[mm]	S* [mm]		[inch]	Innen- Ø [mm]	Außen- Ø [mm]	1.4301	1.4541	
HTS-10-04-38-S	38,00	X1,50		50	68	X	X	X	> 10
		X2,00				X	X	X	
		X2,50				X	X	X	
		X2,60				X	X	X	
		X3,00				X	X	X	
		X3,60				X	X	X	
		X4,00				X	X	X	
		X4,50						X	
		X5,00				X	X	X	
		X6,00				X	X	X	
		X6,30				X	X	X	
HTS-10-04-40-S	40,00	X1,50		50	68	X	X	X	> 10
		X2,00				X	X	X	
		X2,50				X	X	X	
		X3,00				X	X	X	
		X5,00				X	X	X	
HTS-10-04-42-S	42,00	X2,00		65	82	X	X	X	> 10
		X3,00				X	X	X	
		X6,00				X	X	X	
HTS-10-04-42,16-S	42,16	X2,77		65	82	X	X	X	> 10
		X3,56				X	X	X	
		X4,85				X	X	X	
		X6,35				X	X	X	
HTS-10-04-42,40-S	42,40	X1,60		65	82	X	X	X	> 10
		X2,00				X	X	X	
		X2,60				X	X	X	
		X2,90				X	X	X	
		X3,20				X	X	X	
		X3,60				X	X	X	
		X4,05				X	X	X	
	X4,50		X	X	X				
HTS-10-04-43-S	43,00	X1,50		65	82	X	X	X	> 10
		X5,50				X	X	X	
HTS-10-04-44-S	44,00	X2,00		65	82	X			> 10
HTS-10-04-44,50-S	44,50	X2,00		65	82	X	X	X	> 10
		X2,60				X	X	X	
		X2,90				X	X	X	
		X4,00				X	X	X	
		X5,50				X	X	X	
HTS-10-04-45-S	45,00	X1,60		65	82	X			> 10
		X2,00				X			
		X3,00				X	X	X	
		X3,50				X	X	X	
		X5,00				X	X	X	
HTS-10-04-48-S	48,00	X4,00		65	82	X			> 10

Artikel-Nr.	Rohrinnenweite DN		Rohr- nennweite DN	Metallbalg Werkstoff: 1.4541		Werkstoff Nahtloses Rohr nach DIN 17456 / 17458			Baulänge ± 3-5% [mm]
	[mm]	S* [mm]		Innen- Ø [mm]	Außen- Ø [mm]	1.4301	1.4541	1.4571	
HTS-10-04-48,26-S	48,26	X2,77 X3,68 X5,08 X7,14		65	82	X X X X	X X X X	X X X	> 10
HTS-10-04-48,30-S	48,30	X1,60 X2,00 X2,60 X2,90 X3,20 X3,60 X4,05 X5,00 X6,30		65	82	X X X X X X X X X	X X X X X X X X	X X X X X X X	> 10
HTS-10-04-49-S	49,00	X5,50		65	82		X	X	> 10
HTS-10-04-50-S	50,00	X1,50 X2,00 X2,50 X3,00 X4,00 X5,00 X6,00		65	82	X X X X X X X	X X X X X X	X X X X X	> 10
HTS-10-04-51-S	51,00	X2,00 X2,60 X4,00		65	82	X X	X X X	X	> 10
HTS-10-04-52-S	52,00	X1,50 X2,00 X4,00		65	82	X X	X X X	X	> 10
HTS-10-04-53-S	53,00	X1,50 X3,00 X3,60 X4,00 X4,50		65	82	X X X	X X X	X	> 10
HTS-10-04-54-S	54,00	X2,00		65	82	X	X	X	> 10
HTS-10-04-55-S	55,00	X2,50 X5,00		65	82	X X		X	> 10
HTS-10-04-57-S	57,00	X2,00 X2,60 X2,90 X3,50 X4,00 X4,50 X5,00 X6,50		65	82	X X X X X X X X	X X X X X X X X	X X X X X X X	> 10
HTS-10-04-60-S	60,00	X5,00		80	96	X	X	X	> 10

Artikel-Nr.	Rohrinnenweite DN		Rohr- nennweite DN	Metallbalg Werkstoff: 1.4541		Werkstoff Nahtloses Rohr nach DIN 17456 / 17458			Baulänge ± 3-5% [mm]
	[mm]	S* [mm]		Innen- Ø [mm]	Außen- Ø [mm]	1.4301	1.4541	1.4571	
HTS-10-04-60,30-S	60,30	X1,60 X2,00 X2,60 X2,77		80	96	X X X X	X X X X	X X X X	> 10
HTS-10-04-63,50-S	63,50	X2,50 X5,00		80	96		X	X X	> 10
HTS-10-04-64-S	64,00	X2,00		80	96	X		X	> 10
HTS-10-04-65-S	65,00	X2,50 X3,00 X3,50		80	96		X X X	X X	> 10
HTS-10-04-68-S	68,00	X4,00		80	96	X			> 10
HTS-10-04-70-S	70,00	X2,00 X2,90 X3,00 X4,00 X4,50 X5,00 X6,30 X7,00		80	96	X X X X X	X X X X X	X X X X X	> 10
HTS-10-04-73,03-S	73,03	X3,05 X5,16 X7,01		80	96	X X	X		> 10
HTS-10-04-76-S	76,00	X5,00 X6,00		100	124	X X	X X	X X	> 10
HTS-10-04-76,10-S	76,10	X2,00 X2,30 X2,60 X2,90 X3,20 X3,60 X4,00 X4,50 X5,00 X6,30 X7,10 X8,00		100	124	X X X X X X	X X X X X X X	X X X X X X X	> 10
HTS-10-04-80-S	80,00	X2,00 X2,50 X4,00 X5,00		100	124	X X X X	X X X	X X X	> 10
HTS-10-04-82,50-S	82,50	X3,60		100	124		X	X	> 10
HTS-10-04-85-S	85,00	X2,50		100	124		X		> 10
HTS-10-04-88,90-S	88,90	X2,00 X2,30 X2,60 X2,90		100	124	X X X X	X X X X	X X X	> 10

Artikel-Nr.	Rohrinnenweite DN		Rohr- nennweite DN	Metallbalg Werkstoff: 1.4541		Werkstoff Nahtloses Rohr nach DIN 17456 / 17458			Baulänge ± 3-5% [mm]
	[mm]	S* [mm]		[inch]	Innen- Ø [mm]	Außen- Ø [mm]	1.4301	1.4541	
HTS-10-04-90-S	90,00	X5,00		100	124		X	X	> 10
HTS-10-04-97-S	97,00	X4,00		125	154		X	X	> 10
HTS-10-04-100-S	100,00	X3,00 X5,00		125	154		X X	X X	> 10
HTS-10-04-101,60-S	101,60	X3,60 X4,05 X5,00 X5,74		125	154	X X X	X X X	X X X	> 10
HTS-10-04-102-S	102,00	X6,50		125	154	X	X	X	> 10
HTS-10-04-105-S	105,00	X2,50		125	154		X		> 10
HTS-10-04-108-S	108,00	X3,00 X3,20 X3,60 X4,00 X4,50 X5,00 X6,30 X8,00		125	154	X X	X X X X X	X X X X	> 10
HTS-10-04-114,30-S	114,30	X2,60 X3,05 X3,20 X3,60		125	154	X X X	X X X	X X X	> 10
HTS-10-04-121-S	121,00	X4,00		150	178		X	X	> 10
HTS-10-04-127-S	127,00	X4,00		150	178		X	X	> 10
HTS-10-04-133-S	133,00	X4,00 X5,00 X6,30		150	178	X	X X X	X X X	> 10
HTS-10-04-139,70-S	139,70	X4,00 X5,00 X6,30 X7,10		150	178	X X X	X X X X	X X X X	> 10